

## TRAFFIC CONTROL FOR MOBILE OPERATIONS






Sign Details




## Notes

- 1. If the contractor chooses to place more vehicles in the convoy than are shown, these vehicles shall have the truck mounted attenuator and shall be at the contractors expense.
- All traffic control devices shall be in accordance with the "Manual on Uniform Traffic Control Devices" (MUTCD), latest edition.
- Shadow and work vehicles shall display yellow rotating beacons or strobe lights.
- Flashing arrow panels shall be Type B. The panel operation shall be controlled from inside the vehicle.
- 5. Each vehicle shall have two-way radio communication capability.
- 6. When work convoys must change lanes, the shadow vehicle should change lanes first to shadow other convoy vehicles.
- 7. Vehicle spacing between shadow vehicle 1 and shadow vehicle 2 will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the trail vehicle in time to slow down and/or change lanes as they approach the shadow vehicle.
- 8. Sign Colors
  Letters = Black
  Border = Black
  - Background = Orange
- 9. Shadow vehicle 2 may be used as the paint tender vehicle.
- 10. Sign CW21-10A shall only be used during a painting operation.
- 11. On two lane two way roadways, the work and shadow vehicles should pull over periodically to allow motor vehicle traffic to pass.



CW21-10A



Typical Shadow Vehicle 1 & 2 Multi Lane Highways



NORTH DAKOTA	
DEPARTME	NT OF TRANSPORTATION
01-22-92	
REVISIONS	
DATE	CHANGE
02-24-93 06-21-95 06-04-99 10-01-99 07-25-00 05-24-02 12-01-04	General Remove arrow panels W21-4-48 sign General revisions General revisions Major revisions PE Stamp added

This document was originally issued and sealed by MARK S GAYDOS, Registration Number PE-4518, on 12/01/04 and the original document is stored at the North Dakota Department of Transportation